



Canon Pixma GM2070 Single Function Wi-Fi Ink Tank Printer

Product Specification

Brand	Canon
Series	Pixma
Model	GM2070
Type	Single Function Wi-Fi Mono Ink Tank Printer
Available Functions	Print
Printing Resolution	600 (horizontal) x 1200 (vertical) dpi
Print Speed	Document (ESAT/Simplex) : 13.0ipm (black) / 6.8ipm (colour) Document (ESAT/Duplex) : 4.8ipm (black) / 2.8ipm (colour) Document (FPOT Ready / Simplex) : 9s (black) / 14s (colour)
Printable Width	203.2mm (20.32 cm) Borderless: 216mm (21.59 cm)
Printable Area	Bordered Printing : 10 Envelope/DL Envelope: Top 8 mm / Bottom 12.7 mm / Right 5.6 mm / Left 5.6 mm LTR / LGL: Top 3 mm / Bottom 5 mm / Right 6.3 mm / Left 6.4 mm Others: Top 3 mm / Bottom 5 mm / Right 3.4 mm / Left 3.4 mm Bordered Auto 2-Sided Printing : Top / Bottom margin: 5 mm, Left / Right margin: 3.4 mm (LTR: Left: 6.4 mm, Right: 6.3 mm)
Paper Size	Rear Tray : A4, A5, B5, LTR, LGL, Envelopes (DL, COM10), Card Size (91x55 mm) , Custom size : width 55 - 215.9 mm, length 89 - 676 mm Cassette : A4, A5, B5, LTR , Custom size : width 148.0 - 215.9 mm, length 210 - 297 mm
Ink End Sensor	Electrode type and dot count type combined Optional Colour Cartridge Dot count

Network Protocol	TCP/IP SNMP
Network Type	Wired LAN : IEEE802.3u (100BASE-TX) IEEE802.3 (10BASE-T) Wireless : IEEE802.11n / IEEE802.11g / IEEE802.11b
Data Rate	10M/100Mbps (Auto switchable)
Wireless Frequency Band	2.4GHz
Channel	1-13
Range	Indoor 50m (Depends on the transmission speed and conditions)
Security	WEP64/128bit WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)
System Requirements	Windows 10 / 8.1 / 7 SP1 (Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later)