



Printronix P8000 500lpm Printer

Product Specification

Brand	Printronix
Model	P8000
Type	Printer
Print Method	Printronix PrintNet Enterprise remote management software, SAP device support
Function	Printer
Paper Type	Continuous, fan folded, edge-perforation
Print width	13.6" (345mm)
Print Speeds	500lpm
Character Pitch	10, 12, 13.3, 15, 16.7, 17.1, 18, 20
Line Spacing	6, 8, 9, 10.3, n/72, n/216
Graphics Resolution	120 dpi Horizontal, 144 dpi Vertical (max)
Dot Size	16.7 mil (.42mm)
Character Sets	99 plus character sets including ECMA Latin 1, DEC Multinational, IBM Code Page 437 and 850, OCR A, OCR B, UTF8 encoded Unicode
Character Styles	Bold, italic, double wide, double high, overstrike, underline, subscript and superscript
Fonts	NLQ Serif, NLQ Sans Serif, Data Processing, High Speed, OCR A, OCR B

Barcodes	30 resident symbologies, including Code 39, EAN 8/13, UPC A/E, Intelligent Mail, Postnet, Royal Mail, Interleaved 2 of 5, PDF 417, Data Matrix
Power Input Voltage	AC input range 100-240 VAC, 50/60 HZ
Power Consumption	5 watts
Operating Temperature	50° to 104° F, 10° to 40° C
MTBF	10,000 hours at 25% duty cycle and 25% page density
Printer Drivers	Windows XP, 7, 8, 10; Windows Server 2003, 2008/R2, 2012, 2016, 2019, 2022; Linux/UNIX; SAP
Connectivity/Interfaces	Standard: USB 2.0, Serial RS-232, Ethernet 10/100BaseT Optional: Parallel – IEEE 1284 Centronics