



Cisco Switch Model 3560X-24T Layer 3 - 24 x 10/100/1000 Ethernet Ports - Data IP Base

Product Specification

Brand	Cisco
Model	3560X-24T
Product Type	Switch - 24 ports - L3 - Managed
Form Factor	Rack mountable - 1U
Switch Ports	24 x 10/100/1000 Ethernet Ports
Performance	Switching capacity : 160 Gbps
Routing Protocol	RIP-1, RIP-2, HSRP, static IP routing, RIPng
Remote Management Protocol	SNMP 1, SNMP 2, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, TFTP, SSH, CLI
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features	Hot swap module replacement, Layer 3 switching, Layer 2 switching, dynamic IP address assignment , DHCP support, auto-negotiation, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, traffic shaping, Broadcast Storm Control, High Availability, Multicast Storm Control, Unicast Storm Control, Rapid Spanning Tree Protocol (RSTP) support, DHCP snooping, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Access Control List (ACL) support, Quality of Service (QoS), Jumbo Frames support, MLD snooping, Dynamic ARP Inspection (DAI), Per-VLAN Spanning Tree Plus (PVST+), EIGRP Stub Routing
DRAM Memory	256 MB

Flash Memory	64 MB Flash
Interfaces	24 x 10Base-T/100Base-TX/1000Base-T - RJ-45 USB : 1 x 4 PIN USB Type A 1 x console - mini-USB Type B - management 1 x RS-232 - RJ-45 - management 1 x 10Base-T/100Base-TX - RJ-45 - management
Dimensions	Width: 44.5 cm, Depth: 46 cm, Height: 4.5 cm.
Weight	7 kg